



FIRE SUPPRESSIONS SYSTEMS
PATENTED



Thermal Units

Features

- Significantly more effective than alternative extinguishing agents
- Environmentally friendly - Ozone depletion potential (ODP) = 0 - No global warming potential
- Ease of installation – no pressure vessels, piping, or expensive installation manpower
- Very low maintenance
- Provides reliable, cost effective protection for a wide range of fire hazards
- No power required – activates thermally or manually
- Approved by EPA for SNAP listing
- Approved by CSIRO, ECB, MCA, ABS and many more.
- Safe for valuable equipment - will not harm electronic equipment or magnetic media
- Post fire cleanup is minimal - aerosol suspends in air for quick and easy venting after discharge
- Compact – up to a 90% reduction in space and weight requirements

Applications

Due to their fast response time, low fire extinguishing concentration, and environmental safety, Stat-X[®] fire suppression systems may be used in critical applications across a wide range of industries. Aerosol generators are suitable for use in:

- | | |
|-----------------------------|--|
| - Electronic cabinets | - Flammable liquid storage |
| - Switchgear enclosures | - Hazmat storage |
| - CNC machines | - Marine engine rooms and machinery spaces |
| - Data processing equipment | - Small boats |
| - Printing equipment | - High value mobile equipment |

Operation / Description

In the event of a fire, Stat-X generators can be activated either manually or automatically via the integrated thermal detector. Upon activation, the generators produce an exceptionally effective, ultra-fine, potassium based aerosol. Unlike gaseous systems, Stat-X aerosol generators are very cost effective to install and maintain - as they do not require the pressure vessels, piping or expensive installation costs associated with other extinguishing systems. Space and weight requirements are minimal and, in many applications, the small size of the Stat-X aerosol generators makes them the only viable option. On an agent weight basis, Stat-X aerosol is ten times more effective than gaseous agent alternatives. Fire suppression is rapidly achieved through interference between the ultra-fine aerosol particulate and the flame's free radicals – terminating propagation of the fire. Stat-X aerosol generators are virtually maintenance free and have a shelf life of over 10 years. This, coupled to their very low installation cost, makes them an extremely cost effective fire protection solution.



General Specifications:

Model	30 T		60 T		100 T		250 T		500 T	
Aerosol Mass (kg), (lbs)	.03	.07	.06	.14	.10	.22	.25	.55	.50	1.10
Ship Wt./unit Packaging (kg),(lbs)	.26	.60	.35	.80	1.44	3.20	2.72	6.00	3.63	8.00
Length (with actuator) (mm), (in)	109	4.30	142	5.60	152	6.00	168	6.60	218	8.60
Diameter (mm), (in)	51	2.00	51	2.00	76	3.00	127	5.00	127	5.00
Discharge Time(sec)	8.0		8.5		11.5		12.0		21.0	

Activation Temperature Options	70°C (158°F)	95°C (203°F)	123°C (254°F)
Part Number (Order separately from unit)	14650	14651	14652

Coverage Parameters:

Model	Part Number	Aerosol Mass (grams)	Max. Volume Coverage		Max. Area Coverage		Maximum Mounting Height	
			(m ³)	(ft ³)	(m ²)	(ft ²)	(m)	(ft)
30 T	15300	30	0.50	17.66	0.50	5.4	1.0	3.3
60 T	15310	60	1.10	38.85	0.60	6.5	1.8	6.0
100 T	15410	100	1.66	58.62	0.92	9.9	1.8	6.0
250 T	15510	250	4.22	149.0	2.13	22.9	2.0	6.5
500 T	15610	500	9.10	321.0	3.72	40.0	2.5	8.0

For additional information on use of Stat-X systems, please contact your local Distributor or Fireaway LLC.

Operation / Storage Parameters:

Temperature -0° C to +54° C (-65° F to +130° F)
Relative Humidity up to 98% at +35° C (+95° F)



Transportation Classification:

- Classification Code: 4.1
- UN Identification #: UN 3178
- Packaging Group: PGIII
- Shipping Limitations:

- o Ground:
- o Max. weight per unit packaging -
- o Max. weight per unit packaging -

None
Cargo Air 100 kgs (220 lbs)
Passenger Air 25 kgs (55 lbs)

Stat-X is a registered trademark. Manufactured in the USA and sold worldwide exclusively by Fireaway Inc. under license from Techno-TM LLC.



5852 Baker Road, Minnetonka, Minnesota 55345 USA
Tel: 952.935.9745 • Fax: 952.935.9757
www.statx.com

Made in the USA.

Call to discuss your specific requirements with one of our professionals.

